



N110 SERIES
Double Swing

Exterior Storefront Door System

Double-swing commercial entrance system for storefronts, office buildings, retail entrances, and high-traffic exterior access points.

ENGINEERED | PRECISE | RELIABLE

[NIXADOORS.COM](https://nixadoors.com)



DESIGNED FOR WIDER COMMERCIAL ENTRANCES

The N110 Series Double Swing is a prehung aluminum exterior storefront door system built for security, weather performance, and everyday commercial use.

It combines clean architectural lines, laminated safety glass, reliable locking hardware, and smooth self-closing operation.



NIXADOORS.COM



N110 SERIES | DOUBLE SWING | 2

DETAILS THAT WORK EVERY DAY



The N110 Series Double Swing is an exterior storefront door system built for clean design, secure access, weather protection, and wider commercial entry.

BUILT FOR



Storefront Entrances



Office Buildings



Retail Buildings



High-Traffic Commercial Access Points



Medical & Professional Buildings



Double-Swing Access

Active and inactive panels support daily entry, secure closure, and full-width opening when needed.



High-Security Locking System

Commercial-grade locking system supports dependable access control.




60 in. Architectural Pull Handle

Long vertical pull handle adds a clean, modern commercial look.




Advanced Sealing

998-grade silicone sealant helps create a durable weather-resistant bond.




Hidden Fastener Frame

Concealed channels create a clean finish with reduced visible hardware.




ADA Low-Profile Threshold

1/2 in. low-profile threshold supports smoother, more accessible entry.




Integrated Self-Closing System

Adjustable commercial closer supports smooth, controlled closing.



10 in. Kick Plate Protection

Heavy-duty kick plate helps protect against scuffs, carts, and foot traffic.



Laminated Safety Glass

1.3 mm PVB laminated glass improves safety, sound control, and impact resistance.



Continuous Hinge System

Full-height hinge helps maintain alignment and reduce sag.

N110 SERIES Double Swing

CONFIGURATIONS & TECHNICAL OVERVIEW

SWING OPTIONS



FINISH OPTIONS



TECHNICAL SPECIFICATIONS

Series	N110 Series - Double Swing
Door Size	72 in. × 84 in.
Frame Size	78 in. × 87 in.
Door Thickness	1.8 in.
Inactive Panel	Secured inactive panel with authorized release
Lock Type	Commercial-grade high-security locking system
Closing System	Adjustable commercial door self-closer
Glass	1.3 mm PVB laminated safety glass
Frame Material	2.1 mm aluminum with 3.2 mm internal brackets
Handle	60 in. architectural pull handle
Threshold	1/2 in. low-profile threshold
Hinges	Continuous hinge
Kick Plate	10 in. heavy-duty kick plate
Sealant	998-grade silicone sealant

BUILT FOR COMMERCIAL SPACES

Designed for storefronts, offices, retail buildings, professional spaces, and modern exterior commercial entrances.

