



NH110 SERIES
Double Swing

Hurricane-Rated Exterior Storefront Door System

Hurricane-rated commercial double entrance system for storefronts, office buildings, retail entrances, and high-traffic exterior access points requiring wider access.

ENGINEERED | PRECISE | RELIABLE

[NIXADOORS.COM](https://nixadoors.com)



DESIGNED FOR WIDER COMMERCIAL ENTRANCES

The NH110 Series Double Swing is a hurricane-rated prehung aluminum storefront door system built for wider commercial entrances, secure access, weather protection, and daily use. One active panel supports daily entry, while the inactive panel stays secured until full-width access is needed.



DETAILS THAT WORK EVERY DAY



The NH110 Series Double Swing is a hurricane-rated exterior storefront double door system built for clean design, secure access, weather protection, and wider daily commercial use.

BUILT FOR



Storefront Entrances



High-Traffic Commercial Entrances



Office Buildings



Medical & Professional Buildings



Retail Buildings



Hurricane-Rated Commercial Buildings



Double-Swing Access

Active and inactive panels support daily entry, secure closure, and full-width opening when needed.



High-Security Locking System

Commercial-grade locking system supports dependable access control.




60 in. Architectural Pull Handle

Long vertical pull handle adds a clean, modern commercial look.




Advanced Sealing

998-grade silicone sealant helps create a durable weather-resistant bond.




Hidden Fastener Frame

Concealed channels create a clean finish with reduced visible hardware.




ADA Low-Profile Threshold

1/2 in. low-profile threshold supports smoother, more accessible entry.




Integrated Self-Closing System

Adjustable commercial closer supports smooth, controlled closing.



10 in. Kick Plate Protection

Heavy-duty kick plates help protect against scuffs, carts, and foot traffic.



Hurricane-Rated Laminated Glass

Laminated safety glass supports impact resistance, security, and storm-rated exterior performance.



Continuous Hinge System

Full-height hinge helps maintain alignment and reduce sag.

NH110 SERIES Double Swing

CONFIGURATIONS & TECHNICAL OVERVIEW

SWING OPTIONS



FINISH OPTIONS



TECHNICAL SPECIFICATIONS

Series	NH110 Series Double Swing
Door Size	72 in. × 84 in.
Frame Size	78 in. × 87 in.
Thickness	1.8 in.
Rating	Hurricane-rated exterior double door system
Inactive Panel	Secured inactive panel with authorized release
Lock Type	Commercial-grade high-security locking system
Closing System	Adjustable commercial door self-closer
Glass	1.3 mm PVB laminated safety glass
Frame Material	2.1 mm aluminum with 3.2 mm internal brackets
Handle	60 in. architectural pull handles
Threshold	1/2 in. low-profile threshold
Hinges	Continuous hinges
Kick Plate	10 in. heavy-duty kick plate
Sealant	998-grade silicone sealant

BUILT FOR COMMERCIAL SPACES

Designed for storefronts, offices, retail buildings, and hurricane-rated exterior commercial entrances needing wider double-door access.

